



FULL SIZE STRAIGHT STOCK 2023

NO CHANGES OR ALTERATIONS OF RULES TO BE MADE EXCEPT BY EDGE MOTORSPORTS.

NO REFUNDS

IMPORTANT: Each driver, mechanic and any pit crew must sign in at registration desk the day of show and sign the online insurance waiver. Drivers must bring their cars to inspection to have their cars inspected.

DRIVER MUST ATTEND DRIVERS' MEETING PRIOR TO DEMOLITION DERBY OR DRIVER WILL BE DISQUALIFIED.

The Judges decision is final. I agree to participate at my own risk. It is a condition of my participation in the contest that I sign the online insurance waiver.

SPECIAL NOTICE: NO ALCOHOL OR DRUGS ALLOWED IN ANY RESTRICTED (PIT, HOLDING OR PERFORMING) AREA. ANY VIOLATIONS WILL RESULT IN DISQUALIFICATION OF CAR, DRIVER AND CREW. THERE ARE NO REFUNDS FOR NOT FOLLOWING THIS RULE!!!

DRIVERS and MECHANICS are subject to and must obey the following rules and regulations which are set up by the promoter and the track where this event is being held:

1. For all classes not labelled as a "Youth" class, each driver must be a minimum age of 16.

2. The original registered driver must drive the registered vehicle for the entire event. No substituting drivers.
3. Edge Motorsports or promoter reserves the right to approve or reject any and all entries, drivers or pit persons.
4. Only the driver and mechanic who sign the online insurance waiver will be permitted in the pit area or on the track. All drivers, mechanics and pit persons must wear supplied wrist bands at all times. Failure to do so may result in ejection from the event or grounds. Drivers and mechanics are in the pit area at their own risk.
5. Edge Motorsports, the promoter, track owner or fair association will not be held responsible for any loss or damage to any cars, trucks, parts or personal property before, during and after the show.
6. It is highly recommended that each competitor carry their own liability insurance.
7. Drivers and mechanics should report to the Edge Motorsports sign in area at a minimum of 1.5 hours before the scheduled start time.

TYPE OF CAR

Any 6-8 cylinder hardtop automobile or station wagons over 109" wheelbase. STRAIGHT STOCK NO trucks, convertibles, jeeps, vans, **Imperials**, hearses, limousines or checker cabs.

Cars previously ran may be considered too battered and unsafe, resulting in disqualification. If there is in any question regarding the participant's vehicle it is the driver's responsibility to prove make, model, year, engine etc.

RUNNING

Risk: Demolition derbies are hazardous and high-risk sports; therefore, anyone with a health condition, i.e., concussion, heart problems, or who is pregnant should not compete. You are competing at your own risk.

Protect yourself: Work Boots, sport equipment such as, neck brace, knee pads, shoulder pads, hip pads etc. are recommended. No bare exposed skin. All drivers **MUST** wear long pants/coveralls as well as long-sleeved shirts. No exceptions. Working seat belt and racing helmet are mandatory. Helmets **MUST** have chin straps. Goggles or face shields are recommended.

****No motocross style visors****

BRAKES: Vehicles MUST have dependable brakes and must be working properly before entering RING at all times. All boundaries MUST be observed.

NO DRINKING OF ALCOHOLIC BEVERAGES ON TRACK, EMERGENCY VEHICLE AREA OR IN THE PIT AREA. Any driver or pit person under the influence of alcohol or drugs will NOT be allowed in the pit area. This will be strictly enforced.

Careless driving in the pit area could result in disqualification. All cars are to be removed from the fairgrounds or racetrack immediately following the show. Additional safety regulations may be imposed, depending on track and conditions.

PREPARATION OF CAR – REMOVE OR CONVERT THE FOLLOWING PRIOR TO ARRIVING AT FAIRGROUNDS OR TRACK

1. Flammable Material

All carpet, headliner, door panels and ALL other flammable material MUST be removed from inside of the car. Front seat and dashboard may be left in place. Front and rear bumper covers MUST be removed.

2. GLASS/AIR BAGS

All windows, mirrors, trim and air bags must be removed prior to derby event. No loose glass smashed into the bottom of the doors.

3. FIRE EXTINGUISHER

Minimum of 2.5 lbs MUST be within reach of the driver. MUST work and have proper working gauge. Please check gauge on extinguisher before arriving to the event.

4. DOORS AND NUMBERS

Driver's door MUST be reinforced. An optional roof number plate may be securely fastened. Car MUST have a number clearly visible (roof sign, contrasting paint on the doors).

5. BATTERY

Battery must be moved to front passenger floorboard/seat and securely fastened in a box/container clear of all fuel sources. One (1) single car battery. Following inspection it MUST be covered with a non-flammable shield such as air bag or rubber mat. No heavy truck / equipment batteries.

6. GAS TANK

Stock gas tanks must be removed. Steel marine tank, custom fuel cell or certified racing fuel cell ONLY. All tanks must be securely fastened (bolted) down in the middle of the back seat area. Tank must be covered with a non-flammable cover after inspection (air bag, floor mat). No movement can occur during inspection. Any leaks will result in disqualification. No gas tank protectors. Gas tank may be mounted to the post to post bar but not to act in any way as a protector. If tank is mounted to the post to post bar it cannot touch the floor of the car and must be a minimum of 15" from rear sheet metal. NO UNSAFE FUEL TANKS. NO "JERRY CANS".

7. FUEL LINES

All fuel lines MUST have leak proof fitting with steel or rubber lines (no clear lines). No exceptions. Lines should run inside the car. Leaks will result in disqualification. All connections MUST have hose clamps to eliminate leaks. If your fuel system is not safe you will not run.

8. FUEL PUMP

MUST have a safety shut off switch marked in red located in center of windshield or dash area for officials use. Switch to control fuel pump only. Driver's safety. **MANDATORY**. This rule is for fuel injected cars only, does not apply to carbureted cars. MUST be able to be seen by flag staff from 20' away.

9. TRUNK/TAILGATE

Trunks MUST be stock. Trunk lid MUST be stock or removed. Trunk may be tucked in the centre of the trunk area 90°. No other modifying or manipulating of the trunk. Trunk/tailgate must be fastened shut in a max of 6 places using chain, wire or seat belts. If the trunk is fastened shut before tech, a 10" inspection hole is required. No welding. 2x 3/4" threaded rod in trunk/tailgate is allowed but MUST be in the trunk lid NOT the speaker deck area.

10. HOOD

Hoods are not mandatory. Hood must be in stock location or removed. Without hood – use electric fan only – fans directly connected to motor must be removed. A 12" opening must be cut in the center of the hood. Hoods to be fastened in MAX 6 places using chain, strap, wire or belts. Hood may be bolted thru the rad support in 2 places with MAX 3/4" bolts or rod. These bolts can go through the hood, rad support, and frame, must have rubber bushing. These will count for 2 of the 6 places fastening hood closed. **Hoods must remain open for officials' inspection.**

11. BODY PANELS

Metal may be cut from around wheels for clearance. No extra bolts anywhere. No creasing or pre bending.

12. DOOR FASTENING

All doors must be fastened shut with wire, straps, chains, or seat belts in MAX 8 spots per door. No bolting or welding of doors except drivers door can be welded.

13. DOOR PLATES/DOOR BARS

Outside of car may have a 12" X 72" X 1/4" max steel plate applied to driver & passenger doors, bolted in 8 locations with a max of 3/4" bolts. NO "C" CHANNEL OR ANGLE IRON. Driver's door MUST be reinforced.

14. CAGE/ROLL BAR

Single roll bar up each door frame, inside or across outside of the roof. Roll bars going across the roof can be bolted twice through the roof for driver safety. This roll bar may be welded or bolted down to the seat bar or to the floor or frame. A seat bar MAX 3X3" can be bolted or welded behind front seat from side to side to protect driver. No excessive use of materials. Not mandatory. Seat/roll bars not to extend past back of driver's seat. Bar over roof cannot be attached to any other bar on the car except the rear seat bar. A dash bar can also be added but must be 5" away from the firewall. Two side bars can connect dash bar and seat bar creating a square around the driver for safety.

15. INTERIOR MODIFICATIONS

No welding of any inside body support seams or firewall seams. Large holes in car floors must be repaired with same gauge metal and securely fastened. No reinforcement. Broken seats may result in disqualification.

16. BUMPERS

Front bumper only can be replaced with a stock OEM car bumper of any year. Bumper shock can be collapsed and welded. Or you can cut end of the frame off to the front of rad support or sub frame whatever comes first NO mount moving. You can weld a 6" x 6" x 1/4" plate to end of the frame to assist in mounting of the bumper. Your allowed two pieces of flatbar 2" x 4" x 1/4" welded from frame to bumper. No seam welding or loading of bumpers. Front and rear bumper can be wired to hood/rad support or trunk in 4 spots each. These will count as hood/trunk tie downs. NO tubing in end of frame to hold bumper on. Rear bumpers MUST be the stock bumper for vehicle and in stock location or removed. No over welding of front bumper.

17. RADIATOR

Radiators and cooling system must be flushed of anti-freeze and only water added. Overflows for radiator must point downward to the ground. Radiator must be mounted in original position or removed. No screens allowed. (Stock A.C. condensers permitted in original position.) No metal added around the rad for reinforcement. No rad guards.

18. TRANSMISSION COOLER

No transmission coolers.

19. SUSPENSION/STEERING

Suspension MUST remain stock. No modifications, no welding, cars with aluminum spindles can swap to steel spindles with No major modifications. Cars MUST have factory movement. Screw in style spring spacers are ok but movement must occur with one person's effort.

20. FRAMES

No welding the frame, no seam welding. No bolting/pinning frame or subframe. Rusted or **bent** frames may be repaired with a max of 4 plates (4"x4"x1/4"). All frame repairs are to be painted a bright colour and be reported to an official before inspection. Trailer hitch must be removed completely. Rear frame may be notched. No pre bending or shaping of the frame or spare tire well.

21. ENGINES/DRIVELINE

Stock engines/transmissions ONLY. Engines may be swapped Gm in Ford, Dodge ect.

Stock engine and frame mounts MUST be used. No homemade or after markets mounts allowed. No reinforcing motor mounts. Chaining or welding motors down is allowed. 1x5/16" chain per side from engine straight down to frame. Rear differentials may be swapped with stock mounting ONLY. NO truck rearends allowed. If parts are broken and need to be replaced, send a message for clarification. **NO engine protection with the exception of a lower front cradle.**

22. BODY MOUNTS

Stock. Stock bolts, stock bushings. No extra bolts.

23. WINDSHIELD/REAR WINDOW AREA

Front windshield MUST have 1 single steel bar, or chain bolted to cowl and front of roof. No rear window bars. No 9 wire in any windows. Sunroofs MUST be covered with metal or wire mesh.

24. TIRES

Any tire may be used. Drive tires must be filled with air only. Non drive tires may be solid or foam filled. Tires may be doubled. Wheel centres may be welded into rim to change bolt pattern, not to reinforce rim. No full centres. No triple side walls. All wheel weights must be removed. No homemade rims. No bead locks, no valve stem protectors.

"Official's Decision is Final"